

Index

A

- A/A paradox: 53
 AAC: *see* Advanced Audio Coding
 A/B comparison: 53, 55
 absolute pitch: 243
 absolute polarity: 54, 62, 82, 202, 440–441, 453, 459
Absolute Sound, The: xx, 34, 44, 48, 52, 291, 315, 326
 accessories: 16, 126, 152, 403–428
 acoustic
 absorption: 379–386, 395–397, 61
 absorption coefficients: 395–397
 diffraction: 148, 154–155, 194, 311, 421, 462–463
 diffusion: 379–380, 385, 461–462
 dimensional ratios: 385–392
 reflection: 130, 139, 148, 196, 309, 312, 315, 324–326, 347, 362, 364, 367–371, 374, 376–382, 386, 394–395, 402, 415, 443, 461–462
 resonance: 163, 375, 382–383, 386–392
 reverberation: 43, 96, 386, 394–397
 reverberation time: 386, 394–397
 standing waves: 417, 260, 264–265, 373, 382, 386, 393–394, 415
 treatments: 309–310, 359, 375–386, 396–400
 AcousTech: 261
 Acoustic Sciences Corporation (ASC)
 Music Articulation Test Tone: 365, 388–389
 Tube Trap: 368, 371, 382–383, 385–386
 Tower Trap: 380, 382, 386
 Walldamp: 399–400
 AC power conditioner: 14, 52–53, 404, 425–428, 431
 AC power cord: 405–407, 416, 421, 426–428
 AC power line: 38, 251, 421, 425–431
 AC synchronous motor: 251
 active bi-amping: 94–95
 AC wall outlet: 110, 408, 428–431
 Advanced Audio Coding (AAC): 189, 217, 221
 Advanced Audio Distribution Profile (A2DP): 188, 224, 354
 AES: *see* Audio Engineering Society
 AES/EBU digital interface: 106, 179, 183–185, 215, 229, 419
 Aesthetix: 70
 AIFF: *see* Audio Interchange File Format
 air-bearing tonearm: 240, 255
 Air-Motion Transformer: *see* loudspeaker driver
 AirPlay: *see* Apple AirPlay
 air-suspension loading: 144–145
 AIX Records: 326
 ALAC: *see* Apple Lossless Audio Coding
 aliasing: 498
 Allison, Roy: 379
 Allison Effect: 379
 AllMedia: 213, 228
 alternating current: 108, 111, 286, 476, 478, 480
 Ambisonics: 334–336
A Meeting by the River: 322
 American Wire Gauge (AWG): 272, 430
 analog-to-digital conversion: 74, 105–106, 197, 201, 232–233, 402, 507
 anechoic chamber: 362, 394, 442
 anti-skating: *see* tonearm
 Apple AirPlay: 189
 Apple iOS: 189, 214–215, 217, 219
 Apple iPad: 224, 231
 Apple iPhone: 189, 224, 231
 Apple Lossless Audio Coding (ALAC): 189, 217, 220–221, 224, 228, 354
 Apple Mac: 185, 189, 214, 222–227, 230–231
 Apple OS: 223
 aptX: 188–189
 arm-mounting board: 243
 ASC: *see* Acoustic Sciences Corporation
 ASIO: *see* Audio Stream Input/Output
 Astell&Kern: 214, 354–355
 asynchronous sample-rate conversion: 192
 asynchronous USB: 179, 192
 A2DP: *see* Advanced Audio Distribution Profile
 Audience AV: 357
 Audioengine: 178
Audio Engineering Handbook: 378, 456, 458, 460–463
 Audio Engineering Society (AES): 152, 281, 326
 Audio Interchange File Format (AIFF): 220–221, 224, 227–228, 231, 354
 audiophile values: 29
Audiophilia nervosa: 32
 AudioQuest: 3, 184, 186–187, 273, 279, 284–285, 288, 354, 356, 412
 Audio Research Corporation: 92, 330
 Audio Return Channel (HDMI feature): 302
 Audio Stream Input/Output (ASIO): 222–223
 Audio-Technica U.S., Inc.: 256
Audio Technology Fundamentals: 281, 485–488, 490
 audio/video receiver: 90, 294–295, 303, 308, 313–314, 317, 350
 Audyssey: 299, 303
 Auralic: 214–215
 auxiliary bass radiator: *see* passive radiator

Avalon Acoustics: 363

A/V controller:

- analog bypass mode: 299–300
- bass management in: 75, 296, 300, 313
- calibration of: 298–299, 313–315
- DSP room correction in: 299
- in multichannel music systems: 315–316
- multichannel analog input: 301
- multizone: 301
- overview of: 293–297
- surround decoding: 296–301
- 3D capability: 302
- THX certification of: 296
- wireless networking in: 302

AVIA Guide to Home Theater: 388

A/V preamplifier: *see* A/V controller

AVR: *see* audio/video receiver

A/V Room Service, Ltd.: 391

AWG: *see* American Wire Gauge

azimuth: *see* phono cartridge

B

Baerwald, H. G.: 254

Baerwald alignment: 254, 262

BAlabo: 77, 397

balance control: 61, 68, 433

balanced armature driver: 339

balanced connection

- defined: 280–283
- in DACs: 178–179, 182, 184, 206–208, 282–283
- in power amplifiers: 91, 282
- in preamplifiers: 62–63, 78–79, 282

balanced headphone amplifier: 252–253

banana jack: 272, 278

banana plug: 272–274, 277–278, 418

bandpass enclosure: 164–165

Basis Audio: 239, 248, 253

bass management: 75, 176, 296, 299–301, 313, 329–332

bass trap: 383

Bell Telephone Laboratories: 322–323

belt drive (in turntables): 251

Berkeley Audio Design: 178–179

Beyerdynamic: 341

bi-amping: *see* power amplifier

binary number system: 496–497

binaural: 322, 348–349

binding posts: 272, 277–278, 408, 416–418

bipolar loudspeaker: 138, 307, 370

bit transparency (in music servers): 222–223

bi-wire jumpers: 408

bi-wiring: *see* cables and interconnects

Bluetooth: 58, 188–189, 231, 343–344

Blumlein, Alan: 322

Blumlein miking: 322–323

Blu-ray Disc: 167–168, 175–176, 293, 295, 297, 318–319, 321, 323, 329, 335, 504

BNC connection: 179, 183

Boston Symphony Hall: 397

Bowers & Wilkins (B&W): 147–148, 341

break-in (of equipment): 276, 287, 406

bridging (of power amplifiers): 82, 94, 353

Brown, Ray: 41

bypass test (of preamplifiers): 64–65

C

cable elevator: 409

cables and interconnects

balanced and unbalanced: 280–283

bi-wiring: 278–279, 408

break-in: 276, 287, 406

budgeting: 13–16, 275

capacitance and inductance: 257, 279, 283, 285–286, 289, 420, 448, 481–482

choosing: 273–275

cleaning: 406, 416

enhancer: 406

sonic characteristics: 276–277

terminated: 286–287

Caig Labs: 261, 406

capacitor

cartridge loading: 74

DC blocking: 78, 111, 206, 453, 480, 489

described: 284–288

in Class-D amplifiers: 102

in DSD decoding: 205

reservoir (power-supply filtering): 88, 108–110, 114, 426, 429, 480, 485–487

signal filtering: 206, 233, 288, 301, 435, 449

types: 483

Cardas Audio: 338, 409

cartridge: *see* phono cartridge

Cary Audio: 99

CD-4 (Quad format): 323

CD players

budgeting: 13–15

choosing: 168, 173

CD transport: 60, 103, 160, 183, 190, 210, 272

CD treatment: 405, 410–411

center channel: 304–305, 311, 314, 333

CEntrance: 357

Channel D Software: 187, 224, 231, 234

channel separation: *see* crosstalk

Chesky Records: 330–331, 384, 469
 chuffing: 147
 Clarke, Stanley: 41
 Class-A amplifier operation: *see* power amplifier
 Class-A/B amplifier operation: *see* power amplifier
 Class-D amplifier operation: *see* power amplifier
 Classé Audio: 296
 clipping: *see* power amplifiers
 clocking: *see* digital audio
 coaxial (concentric) loudspeaker driver: *see* loudspeaker drivers
 Cohen, Alan: 281, 485–488, 490
 coincident microphone techniques: 322
 Colloms, Martin: 47–48, 129, 148–149, 156
 comb filtering: 347, 349, 377–378, 461, 463, 469
 common-mode rejection: 207, 280, 494
 Compact Disc: 168, 173–174, 193, 199, 210, 236, 498, 504–506
 compliance: *see* phono cartridge
 compression driver: 142
 concentric driver: *see* loudspeaker drivers
 constrained-layer damping: 247–248
 Consumer Electronics Show: 291, 327
 contact cleaning: 404, 406–407, 416–418, 420–421, 430–431
 critical listening: 27, 29, 32–33, 49–55
 critical listening setup procedure: 52
 Critical Mass Systems: 423
 crossfeed circuit: 346
 crossover distortion: *see* zero crossing distortion
 crossovers
 digital domain: 158–160
 electronic: 94–95, 150, 161, 165
 frequency and slope: 155–157, 165, 373
 in A/V controllers: 296, 299–300, 302
 in loudspeakers: 94–95, 121–122, 127, 131, 136, 143, 155, 194, 369, 420, 479–480, 482
 in subwoofers: 105, 161–162, 165, 357
 crosstalk: 353, 435–437, 440, 449–450
 cryogenic treatment: 427
 cumulative spectral decay: 446–447

D

DAC: *see* digital-to-analog converter
 damping factor: *see* power amplifier
 Data Conversion Systems (dCS): 187, 191, 194, 205
 dBpoweramp: 226–228
 dBW power rating: 86–88
 DC blocking capacitor: *see* capacitors
 DC servo: 78, 111, 206, 453
 decibel: 463–465

dedicated AC line: 428–429, 431
 De Forest, Lee: 98
 Delos: 323
 Delta-Sigma DAC: 204–205
Denon Anechoic Orchestral Recording: 394
 DeoxIT: *see* Caig Labs
 Devialet: 104–105
 dielectric absorption: 284
 Dielectric-Bias System: 288
 differential amplifier: 78, 207, 280–281, 494
 diffraction: 148, 154–155, 311, 421, 462–463
 digital audio
 clocking: 167, 175, 179, 181, 185–187, 189–192, 202, 210, 229, 253–254, 507–510
 dither: 196, 203–204, 222, 449, 503–504
 error correction: 210, 226, 231, 454, 505–506
 filtering: 178, 181, 192–195, 201–204, 207–208
 high-resolution: *see* high-resolution digital audio
 quantization: 195–197, 205, 452, 497–498, 501–503
 sampling: 192–194, 197, 497–501
 digital-domain volume control: 181, 419
 Digital eXtreme Definition (DXD): 196, 215, 221, 354
 digital interface: *see* AES/EBU, Ethernet, S/PDIF, TosLink, USB
 Digital Living Network Alliance (DLNA): 230–231
 digital loudspeaker: 158–160, 188
 digital power amplifier: 98, 102–104
 digital preamplifier: 60, 74, 183
 digital signal processing (DSP): 103–104, 158–160, 194, 201, 203, 299–301, 333, 347, 349, 400–402, 453, 510
 Digital Theater Systems (DTS): 60, 75, 293, 297, 300
 DTS ES Discrete: 318
 DTS HD: 75, 116, 293–295, 298, 303, 318
 DTS HD Master Audio: 75, 176, 293–295, 298, 317
 DTS Neo:6: 317, 373
 digital-to-analog converter (DAC)
 balanced outputs on: 178–179, 182, 184, 206, 208
 choosing: 13–15, 168–173, 177–182
 desktop: 356–357
 DSD decoding: 180, 187–188
 external clocking: 181, 190–192
 features: 178–182
 in integrated amplifiers and preamplifiers: 8, 57–58, 60, 104–105, 167
 networked: 182, 215–216
 sound quality: 31, 128, 169–173
 source switching in: 179–181
 technical description: 201–208, 506–510
 technical performance: 448–454
 volume control: 68, 180–182, 419

wireless: xviii, 106, 188–189, 213–214, 167, 182, 229
 Digital Transmission Content Protection: 188
 dimensional ratios (room): 385, 389–392
 dipolar loudspeaker: *see* loudspeakers
 direct-attached storage (DAS): 225
 direct-coupled circuit: 78, 111, 206, 453, 471
 direct drive (in turntables): 251
 Direct Stream Digital (DSD)
 conversion to PCM: 180, 196, 233
 decoding: 180, 198, 205, 354
 download: 175, 180, 212, 224
 encoding: 102, 175, 196–199, 205
 multichannel: 173–175, 325
 multiple rate: 180, 214–215, 354
 on SACD: 197–199
 over PCM (DoP): 187–188
 technical description: 197–199
 direct-to-disc recording: 259, 267, 269–270
 dither: *see* digital audio
 DLNA: *see* Digital Living Network Alliance
 Dolby Digital: 60, 75, 176, 201, 221, 293, 297–298, 300–301, 316–318, 323, 330, 349, 510–511
 Dolby Digital EX: 317–318
 Dolby Digital Plus: 75, 293–295, 298, 303
 Dolby Labs: 317
 Dolby Pro Logic: 75, 293, 295, 301, 303, 308, 316–317, 333
 Dolby TrueHD: 75, 176, 293–295, 298
 DoP: *see* Direct Stream Digital
 download: 168–169, 175, 180, 187, 197, 210–213, 217–219, 227–228, 230
 DSD: *see* Direct Stream Digital
 DSD over PCM (DoP): *see* Direct Stream Digital
 DSP: *see* digital signal processing
 DSP room correction: 106, 183, 299, 400–402
 DTS: *see* Digital Theater Systems
 DXD: *see* Digital eXtreme Definition
 DVD-Audio: 168, 175, 321, 335
 dynamic headroom: *see* power amplifier
 dynamic range: 34, 45–46, 195, 211

E

earbuds: 338
 Eargle, John: 322
 earphones: 338–340, 342, 353
 EARS (NAD technology): 333
 electromagnetic driver: 128–129
 electromagnetic induction: 256, 477–478
 electromagnetic interference (EMI): 425
 electronic crossover: *see* crossovers
 electrostatic headphones: 344–345, 347

electrostatic loudspeaker: *see* loudspeaker
 EMI: *see* electromagnetic interference
 equalizer: 2, 32, 150, 231–232, 302, 401
 equal loudness contours: 466–467
 equipment rack: 240, 247, 260, 384, 386, 404, 409–410, 415–416
 Erskine, Peter: 209
 Ethernet: 106, 179, 182, 186–187, 213, 215, 225
 Exact Audio Copy: 226–228

F

Faraday, Michael: 109
 Fast Fourier Transform (FFT): 439–440, 443, 446, 452–454
 Federal Trade Commission (FTC): 90
 feedback (acoustical): 246, 339
 feedback (electrical): 4, 99, 111, 114, 353, 440, 489
 Feickert: 262
 Ferrofluid: 126
 file formats: *see* music servers
 FireWire: 188, 223, 225–226, 272
Fi: The Magazine of Music and Sound: xx
 5.1-channel sound: 293–295, 297, 301, 316–319
 FLAC: *see* Free Lossless Audio Codec
 Fletcher, Harvey: 323, 466
 Fletcher-Munson curves: 466
 flutter: 243, 251, 507
 flutter echo: 376, 385
 Fluxbuster: 412
 Focal: 129
 Foobar2000: 223–224
 45/45 system: 323
 Fosgate: 262
 4k video: 298
 Free Lossless Audio Codec (FLAC): 179, 212–213, 220–221, 224, 227–228, 354, 405
 Fremer, Michael: 260, 264
 full-range driver: *see* loudspeaker drivers

G

Gerzon, Michael: 323
 gimbal bearing (in tonearms): 253
 Gomez, Eddie: 41
 Gordon, Dexter: 306
 Gracenote CDDB: 219, 228, 234
 Grado Labs: 342
 Graham tonearm: 253
 ground isolator: 407
 ground loop: 407, 429–430

H

- Haas Effect: 470
- Hafler, David: 114
- half-speed mastering: *see* vinyl
- Hancock, Herbie: 327
- hard-disk drive (audio storage on): 103, 167, 179, 210, 212–215, 224–227, 230–231, 321
- Harman International: 333
- harmonic distortion: 3, 28, 66, 90, 108, 112, 115, 254, 419, 434–435, 439–440, 491–492
- harmonic-distortion spectrum: 419
- HDCCD: *see* High Definition Compatible Digital
- HDMI: 187–188, 272, 297–298, 302, 319, 329
- “head-in-a-vice” syndrome: 334
- headphone amplifiers: 62, 77, 393, 346, 350–356
- headphone jack: 77, 178, 352
- headphones
 - amplifier matching: 343, 350–353
 - balanced drive: 352–353
 - binaural listening: 348–349
 - choosing: 340–344
 - circumaural vs. supra-aural: 340–341
 - electrostatic: 344–345
 - multichannel: 349
 - noise-canceling: 343
 - open-back vs. closed-back: 341–342
 - planar-magnetic: 344–345
 - supra-aural: 340–341
 - wireless: 343–344
- head-related transfer function (HRTF): 347–349, 469
- Hegel: 354
- Heil Air-Motion Transformer: 133–134
- Helmholtz resonator: 383
- Hertz, Heinrich: 457
- Heyser, Richard: 28, 442
- Heyser Box: 28–29
- High Definition Compatible Digital (HDCCD): 182, 197, 199–201, 222
- High Performance Loudspeakers*: 129, 148–149, 156, 447
- high-resolution digital audio
 - advantages: 192–196, 227
 - caveats: 196–197, 211–212
 - downloads: xviii, 169, 187, 211–212, 227, 495
 - interfaces: 185, 187–188, 272, 298, 354
 - multichannel: 168, 176, 298, 317–319, 321, 326
 - on Blu-ray Disc: 168, 176
 - on portable devices: 353–355
 - on SACD: 168, 173, 175, 495
 - on smartphones: 216–217
 - over HDMI: 298
 - storage: 224–225, 233
 - subscription service: 218
 - wireless transmission: 189, 214
- Holland, Dave: 41
- Holman, Tomlinson: 327
- Holt, J. Gordon: 38, 135
- home audition of components: 11, 24–25, 122
- home theater
 - calibration: 313–315
 - combining with music system: 61, 84, 315–316
 - controllers: 60, 75, 84, 176, 188, 293, 295–303
 - loudspeaker: 304–308
 - power amplifier: 303–304
 - subwoofer: 293–297, 299–302, 304, 306, 308
 - surround-sound formats: *see* Dolby, DTS
- horn loudspeaker: *see* loudspeaker driver
- hybrid tube/solid-state power amplifier: 82, 112
- hybrid tube/solid-state preamplifier: 60, 67
- hyperelliptical stylus: 258

I

- IEEE1394: *see* FireWire
- IMD: *see* intermodulation distortion
- impedance
 - defined: 75, 88, 441, 480
 - in DACs: 185, 206, 448, 480–481
 - in digital interfaces: 185
 - in loudspeakers: 85, 90, 92–94, 97, 100, 112–114, 350–356
 - in phono preamplifiers: 73–74, 257
 - in power amplifiers: 21, 97, 99, 101, 111–112, 273, 290, 437, 480
 - in preamplifiers: 75–76, 88, 105, 434, 480–481
- impedance curve: 15, 106, 441–442
- impulse response: 443–444, 446
- inductance: 279, 283, 285–286, 289, 420, 441, 477–480, 482
- in-ear monitors: 338–340
- input overload: 72, 434
- intensity stereo: 34
- interaural crosstalk: 382
- interconnects: *see* cables and interconnects
- intermodulation distortion (IMD): 440, 452, 491
- Internet download: *see* download
- Internet Radio: 58, 182, 217
- iPad: *see* Apple iPad
- iPhone: *see* Apple iPhone
- iPod: *see* Apple iPod
- Isobarik: 144, 148
- iTunes: *see* Apple iTunes
- I²S interface: 187–188

J

Jarrett, Keith: xvi

JBL: 333

JFET: 22, 471, 491

jitter

explained: 507–510

 in DACs: 178, 185, 192, 196, 202, 206, 448,
 480–481 in digital interfaces: 183–186, 189–192, 196,
 202, 507–510

measurement of: 453–454

sonic effects: 192–193

Johnson, Keith: 199

Johnson, William Zane: 92

JRiver Media Center: 201, 233–224

JVC: 205, 323

K

KEF: 126–127

Keroes, Herbert: 114

Klipsch, Paul: 85

Klipschorn: 85

knuckle-rap test (of loudspeakers): 153

L

Level matching: 53, 55–56, 123

Lexicon: 333

LFE channel: *see* low-frequency effects

LIM Detector: 453

linear-crystal copper: 283

linearity (in DACs): 204–205, 450–452

line source (loudspeaker): 130

Linn Products: 95, 148, 237, 252

Listening Environment Diagnostic Recording
(LEDR): 384, 469

listening height: 122, 127, 132, 158, 360, 366, 376, 446

litz cable: 286

localization (of sound): 34, 165, 307, 312, 319, 322, 367,
374, 469

Löfgren, E: 254, 262

Löfgren alignment: 254

Logic 7: 333

Long, Ed: 155

long-wall speaker placement: 368–369

Louden, M. M.: 391–392

loudness compensation: 159

loudspeaker

anechoic response: 149, 362, 442–443

 bipolar: *see* bipolar loudspeaker

break-in: 420–421

budgeting: 12–15

choosing: 118–122

 crossover: 94–95, 121–122, 127, 131, 136, 143,
 155, 194, 369, 420, 479–480, 482 digital: *see* digital loudspeaker dipolar: *see* dipolar loudspeaker

dynamic/electrostatic hybrid: 134–137

dynamic/ribbon hybrid: 133

 electronics matching: 85–88, 90–91, 99–100,
 119–120, 140–142 for home theater: *see* home theater

for multichannel music: 330–331, 374–376

 impedance: *see* impedance

line-source: 130

omnidirectional: 138–139

phase angle: 441–442, 482–483

 placement: 45, 118, 132, 136–137, 158, 163,
 307–314, 328, 330–332, 335, 359–376

radiation pattern: 130–131, 135–138, 307, 371

room matching: 9, 118–119, 132, 136

 sensitivity: 13–15, 55–56, 90–91, 94, 97–98, 100,
 107, 114, 119, 128–129, 131, 139–140, 142,
 45–148, 164–165, 303–304, 332, 441–442

specifications and measurements: 441–447

spikes: 166, 361, 367, 375, 415, 420, 423–424

stand: 166, 306

toe-in: 312–313, 360, 366–367, 376, 404, 446

loudspeaker driver

air-motion transformer (AMT): 133–134

coaxial (concentric): 126–127

dynamic (moving coil): 124–128

electrostatic: 124, 134–138

full-range: 143–144, 339

horn: 98, 100, 139–143

passive radiator: 147

planar-magnetic: 129, 136

quasi-ribbon: 130

ribbon: 124, 129–133

servo drive: 150–151

loudspeaker enclosure

 alignment (Q): *see* Q

bracing: 154

diffraction: 148, 154–155, 311, 421, 462–463

infinite baffle: 144–145

reflex loading: 144–147, 164

 resonance in: 39, 48, 121, 131, 144, 151–154,
 166, 289, 410, 446–447

transmission line: 147–148, 164

low-frequency effects (LFE): 293, 297, 300, 308, 316, 330

LP: *see* vinyl

Lucasfilm: 302, 308, 317

M

Mac: *see* Apple Mac
 Magico: 141, 153
 Magnepan: 130, 132
 magnetic suspension (of turntables): 249
 MartinLogan: 134–135, 137
 MASH (1-bit DAC): 204
 masking (psychoacoustic effect): 470
 mass loading: 166
Master Handbook of Acoustics, The: 383, 392, 397
 Mastering Lab, The: 268
 MATT test: *see* Music Articulation Test Tone
 Maximum Length Sequence System Analyzer (MLSSA): 443
 Mayorga, Lincoln: 269
 MBL: 138–139
 McCormack, Steve: 424
 McGrath, Peter: 325
 measurements vs. listening: 27–29
 MediaMonkey: 223–224
 Meitner, Ed: 453
 Meridian Audio: 160, 188, 194–195, 213, 333, 336
 metadata: *see* music servers
Microphone Handbook, The: 322
 microphony: 404, 415, 418, 422
 microridge (stylus shape): 258
 MIT: *see* Music Interface Technologies
 Mod Squad, The: 424
 Monster Cable Products: 298
 MOSFET: 112, 491
 moving-coil cartridge: *see* phono cartridge
 moving-coil driver: *see* loudspeaker driver, dynamic
 MP3: 179, 221, 224, 227, 354
 multichannel:
 electronics: 59–60, 75, 81, 294–296, 301, 303–304, 315–316
 formats: 168, 175–176, 188, 301, 330
 headphones: 349
 history: 321–324
 loudspeaker: 177, 293–294, 304–309, 328–332
 source: 168, 175–176, 188, 301, 330
 see also home theater
 Museatex: 453
 Music Articulation Test Tone (MATT): 365
 Music Direct: 266, 408–409, 424
 Music Genome Project: 218–219
 Music Interface Technologies (MIT): 286–287
 Music Logic: 333

music server
 bit transparency: 222–223
 downloading: 168–169, 175, 180, 187, 197, 210–213, 217–219, 227–228, 230
 file formats: 220–221; *see also* AAC, AIFF, FLAC, MP3, Ogg Vorbis, WAV
 LP ripping: 232–234
 metadata: 186–187, 213, 219–220, 228, 230–231, 234, 319
 music-management software: 223–224
 overview: 168–169, 209–210
 ripping to: 175, 210, 213, 227
 sound quality: 210–211
 storage: 182, 214–216, 220, 223–226, 229–232, 302, 355
 tagging: *see* metadata
 turnkey: 168, 212–216
 with music subscription services: 217–218
 Mystère: 113

N

NAD Electronics: 103–104, 333
 Naim Audio: 215
 Nautilus technology (Bowers & Wilkins): 147
 NC rating: *see* noise criterion
 negative feedback: *see* feedback, electrical
 network-attached storage (NAS): 182, 214–216, 220, 223, 225–226, 229–232, 302, 355
 networked audio: vxiii, 8, 58, 84, 168, 179, 182, 186–189, 214–217, 225–226, 229–231, 297, 302, 354
 new old stock: 67
 Nimbus: 335
 Nitty Gritty: 412
 noise-canceling headphones: *see* headphones
 noise criterion (NC) rating: 399
 noise shaping: 198, 205, 450–451
 NOS: *see* new old stock
 NuForce: 102
 Nyquist, Harry: 498
 Nyquist theorem: 192, 498

O

Ogg Vorbis: 221, 354
 Ohm's law: 94, 472–473, 476, 478, 481
 Ohno Continuous Casting: 283
 omnidirectional loudspeaker: *see* loudspeaker
 1-bit D/A converters: 204–205, 450–451
 180-gram vinyl: *see* vinyl
 op-amp: *see* operational amplifier

operational amplifier: 76, 78, 111, 206, 282, 301, 351, 493–494

OTL: *see* output-transformerless

output impedance

defined: 480–482

in power amplifiers: 21, 97, 99–100, 273, 290, 437

in preamplifiers: 75–76, 434, 492–493

in source components: 185, 206, 289, 448

output-transformerless (OTL) amplifiers: 113

oxidation (of connectors): 285, 406, 416

oxygen-free copper: 283

P

Pacific Microsonics: 199, 201

Pandora: 217–219, 302

panel absorbers: 383, 386

passive bi-amping: 94–95

passive level control: 60, 65, 434, 448

passive radiator: 147

Pass Laboratories: 101, 107

Patitucci, John: 41

peak power (in amplifiers): 89, 439

Pearson, Harry: 48

pentode tube: 98, 114, 493

perceptual coding: 353, 510–511

Perfect Sound Forever: 236

Perfect Vision, The: xx

Personal Knowledge: 27, 32

Pflaumer, Michael: 199

phantom imaging: 305, 323, 327, 374

phase (defined): 457–461

phase-and-time-coherent loudspeaker: 143, 156–157, 443

phase angle: 441–442

phase cancellation: 138, 373, 393, 420

phase control (on subwoofer): 372–373

phase in AC power: 430

phase-locked loop (PLL): 190, 202, 251, 510

phase (loudspeaker connection): 420–421

phase shift: 193–194, 202

phase splitter: 78, 99, 111, 206–208, 282

phono cartridge

azimuth: 252, 262–263, 441

compliance: 243–245

demagnetizing: 265, 412–413

loading: 69–70, 72–74, 105, 232

moving-coil: 72, 256–257, 265, 413, 434, 477

moving-magnet: 72–73, 256–257, 265, 413, 434, 477

output voltage: 72–73, 257, 434

phono-stage matching: 71–74, 232–233, 257, 434

strain-gauge: 257

theory of operation: 256–257, 447

tracing distortion: 258

tracking ability: 259

phono preamplifier (stand alone component): 8, 60, 69–74, 433–434

phono preamplifier (within full-function preamplifier): *see* preamplifier

phono-stage gain: 71–73, 257

pink noise: 332, 420

pinna: 347, 349, 469

planar loudspeakers (defined): 124, 130

planar-magnetic driver: *see* loudspeaker driver

planar-magnetic headphones: *see* headphones

platter: 239, 243, 246–251, 263, 413

platter mat: 250, 413

PLL: *see* phase-locked loop

Pohlmann, Ken: 202, 204, 499–500, 502–505, 511

point-source loudspeaker: 124, 127, 130–131, 137

Polanyi, Michael: 27, 32

polarity inversion: *see* absolute polarity

power amplifier

balanced inputs: 93, 198

bi-amping: 77, 82, 94–95, 151, 161

bridging: 82, 94, 353

budgeting: 13–15, 83

choosing: 51, 87–88, 90–91, 96–98, 100, 119–120

Class-A: 78, 82, 101, 104, 106–109, 111, 489–491

Class-A/B: 82, 107–108, 111, 489–491

Class-D (switching): 82, 101–104, 199, 356

class of operation: 82, 99, 101, 103–108, 111, 113, 199, 356, 471, 489–491

clipping: 112, 115, 437–439

damping factor: 289–290, 350–351, 437

digital: 98, 102–104

dynamic headroom: 88, 201, 439

gain: 95, 437

home theater: *see* home theater

input sensitivity: 437

loudspeaker matching: *see* loudspeaker, electronics matching

monoblock: 81, 83, 85, 94, 99, 102, 105, 294, 303

MOSFET: *see* MOSFET

output impedance: 21, 97, 99–100, 273, 290, 437

output-power ratings: 85–91, 437–439

output stage: 82, 88, 99, 101–108, 112–114, 415, 437, 489–491, 493

output transformer: 92, 112–114, 418, 437
 power bandwidth: 89, 438
 tube replacement: 92, 113–114
 tubes vs. transistors: 92–93
 zero-crossing distortion: 108
 power transformer: 83–84, 88, 108–109, 113, 151, 304, 407, 422, 428, 476, 478, 484, 486, 491
 preamplifier
 balance control: 61, 68, 473
 balanced connection: 62–63, 78–79, 282
 digital: 60, 74, 183
 gain: 61, 64–65, 67, 73, 76, 78, 433–434
 hybrid (tube and solid-state): 60, 67
 input overload: 72, 434
 line-stage: 59, 61, 68–69, 71, 73, 433–434, 448
 multichannel: 60, 75, 177, 329–330
 phono stage: 8, 57, 59, 70–74, 433–434
 RIAA equalization: *see* RIAA equalization
 theater pass-through: 61, 84, 300, 315–316
 tubed: 60, 65–68
 12V trigger: 61–62, 69
 pre-preamplifier: 72
 presence region: 76
Principles of Digital Audio: 202, 204, 499–500, 502–505, 511
 Pro-Ject: 70, 238
 protractor (tonearm alignment): 243, 254, 261–263, 414
 PS Audio: 188, 408
 PSB Speakers: 342
 psychoacoustics: 159, 194, 327, 466, 470, 511
 pulse-code modulation (PCM): 103, 179–180, 187–188, 196, 205, 220–221, 224, 233, 298, 317, 321, 354, 499, 504
 pulse-width modulation (PWM): 102–103, 197, 504
 Pure Audio: 77
 Pure Music: 220–221, 223–224, 231–232
 push-pull output stage: 82, 92, 99–101, 106–107, 112, 114, 438, 271, 490

Q

Q (Quality factor): 149
 Quadraphonic: 321, 323
 quantization: 192, 195, 198, 205, 452, 497–498
 quantization error: 501–504
 quarter-wavelength trap: 384
 quasi-ribbon driver: 130–131

R

rack: *see* equipment rack

Radialstrahler: 139
 radio frequency interference (RFI): 183, 406
 RadioShack SPL meter: 314, 332
 Raidho Acoustics: 133
 record care: 264–267
 record clamp: 250, 413
 record-cleaning machine: 232, 265–267, 412, 414
 Recording Industry Association of America (RIAA): 60
 Red Book (CD specification): 174, 506
 Reference Recordings: 34
 reflex loading: *see* loudspeaker enclosures
 Reger, Max: 31
 regulation (power supply): 486
 resonance
 acoustic: 41, 63, 147, 163, 375, 382–383, 386–392, 396
 in listening rooms: *see* room resonance modes
 in loudspeaker drivers: 129, 135, 143, 149–150, 157, 289, 344
 in loudspeaker enclosures: *see* loudspeaker enclosure
 in vinyl playback: 244–246, 253, 255, 259, 263, 422
 Revel: 142
 reverberation: 36, 43, 196, 241, 243, 324–326, 332–333, 386, 394–397, 399, 502, 504
 RFI: *see* radio frequency interference
 RFI filter: 406
 Rhapsody: 58, 217, 302
 RIAA: *see* Recording Industry Association of America
 RIAA accuracy: 70, 435
 RIAA equalization: 60, 70–71, 233, 435
 ribbon driver: *see* loudspeaker driver
 Ring DAC: 205
 ripping: 105, 210, 213, 220–221, 226–228
 ripping NAS: 226
 Ritter, Michael: 199
 RMS (root mean square): 89–90
 room correction: *see* DSP room correction
 room gain: 362, 368
 Room Optimizer: 365, 392
 room resonance modes: 163, 271, 375, 379–380, 382–383, 385–392
 RPG Diffusor Systems: 365, 371, 379–380, 385–386, 392
 RT₆₀: 394–397
 rule of thirds (loudspeaker placement): 364–365
 Rutter, John, *Requiem*: 34

S

- Sabine, Wallace Clement: 397
 SACD: *see* Super Audio Compact Disc
 Sax, Doug: 259
 server: *see* music server
 servo-driven woofer: 150–151, 164
 SET: *see* single-ended triode
 7.1-channel sound: 75, 176, 293–297, 301, 308, 316–317, 319
 Sheffield Lab: 259, 269
 Shibata (stylus shape): 258
 Shishido, Nobu: 99
 shorting plug: 93, 408
 Shunyata Research: 410, 426–427, 430
 sidewall reflections: 309, 364, 367, 377–382, 385–386
 signal/noise ratio: 72–73, 195, 198, 434–435, 437, 440, 467, 502–504
 single-ended solid-state amplifier: 98, 101
 single-ended triode (SET) amplifier: 56, 86, 90, 92, 98–99, 101, 492
 single-presentation listening: 54–55
 sins of commission/omission: 30, 41
 six-nines copper: 283
 60Hz hum: 415, 429, 435, 484
 skating: *see* tonearm
 skin effect (in cables): 285–286
 Skyline diffuser: 371
 slew rate: 353, 492
 Smyth Virtual Surround (SVS): 346–348
 Sonex: 384
 Sony Corporation: 173–175, 188, 197–199, 202, 323, 325, 337
 Sorbothane: 248, 407, 424
 sound-pressure level (SPL): 85, 119, 314, 332, 351, 463–466, 467
 sound-pressure level (SPL) meter: 314, 332, 388
 soundstaging: 34, 38, 42–45
 Sound Transmission Class (STC): 399
 S/PDIF digital interface: 179, 183–187, 190–191, 202, 229, 272, 509
 spectral analysis: 449–453
 spikes (loudspeaker): 166, 361, 367, 375, 415, 420, 423–424
 sprung turntable: *see* turntable
 SQ (quadraphonic system): 323
 standing waves: 147, 260, 364–365, 373, 382, 386, 393–394, 415
 Stax: 344–345, 347
 STC: *see* Sound Transmission Class
 stepped attenuator: 76–77, 84, 421
 step-up transformer: 72, 136
 step response (loudspeaker measurement): 444
Stereophile: xx, 17, 38, 48–49, 135, 365, 435–436, 438–447, 449–451
 stereo receiver: 84
 Stillpoints: 442
 Stokowski, Leopold: 323
 Story, Mike: 194
 strain-gauge cartridge: *see* phono cartridge
 streaming audio: xviii, 30, 58, 84, 182, 189, 214–218, 223, 230, 297, 321, 354
 structure-borne vibration: 246–248, 260, 407
 ST-Type glass-fiber optical interface: 179, 183
 stylus: 244, 248–249, 252–258, 261–265, 411, 414
 stylus pressure gauge: 261, 411
 subscription-based music service: 58, 167–168
 subwoofer
 crossover: 105, 161–163, 165, 299, 302
 design: 164–165
 in home theater: 15, 75, 293–297, 300, 302, 306, 308, 370
 overview of: 160–164, 176–177, 372
 passive vs. active: 95, 88, 161–163, 308
 placement and setup: 314, 371–373
 Sumiko: 70, 238, 412
 Super Audio CD
 bass management in player: 176–177
 choosing: 168
 DSD encoding on: 102, 175, 197–199
 hybrid disc: 173–175
 multichannel audio on: 168, 173, 188
 players: 167–168, 173–176, 188
 technical description: 173–175
 with digital amplifiers: 102
 surround-back loudspeaker: 295, 301, 303, 308
 surround loudspeaker: 15, 45, 61, 177, 292–295, 297, 301, 303, 306–311, 314–315, 317–318, 328–334
 surround sound: *see* multichannel audio
 surround-sound processor: *see* A/V controller
 sweet spot: 30, 134, 334, 336, 361
 switching amplifier: *see* power amplifier
 system matching: 20–22, 24, 83, 120, 170, 243

T

- tagging (music files): *see* metadata
 tape-output jacks: 77
 Taylor, James: 327
 terminated cable: 286–287
 THD: *see* total harmonic distortion
 theater bypass: *see* theater pass-through

- theater pass-through: 61, 84, 300, 315
 Thiel Audio: 125–126, 155
 3D video: 302
 THX: 296, 302, 306, 313, 327
 Tiefenbrun, Ivor: 237
 time-delay spectrometry (TDS): 442–443
 Tiptoes: 424
 toe-in: *see* loudspeaker
 tonal balance: 35
 tonearm
 air-bearing: 240, 255
 anti-skate: 221–227, 230–231, 252, 255, 263
 bearings: 240, 252–255
 cable: 74, 257, 261, 263, 412–413
 effective mass: 243–245, 253, 259
 offset: 254–255, 261, 263, 412–413
 overhang: 243, 253–255, 261, 263
 pivoted: 252–255
 tangential-tracking: 240, 252, 255
 tracking error: 254–255, 261
 twelve-inch: 254–255
 unipivot: 253
 tone controls: 61
 tone defeat switch: 61
 Toole, Floyd: 470
 TosLink: 173, 179, 183–185, 229, 298
 total harmonic distortion (THD): 3–4, 90, 99, 177, 434–436, 438–440, 491
 tracing distortion: *see* phono cartridge
 tracking ability: *see* phono cartridge
 tracking error: *see* tonearm
 transformer:
 as volume control: 77
 impedance matching: 112–113, 131, 141
 in balanced circuits: 281
 isolation: 407
 output: 92, 112–114, 418, 437
 power: 93–94, 98, 108–109, 113, 151, 304, 356, 407, 415, 428, 442, 471, 476, 478, 484–487, 491
 transient response: 46, 134, 136, 147, 149–150, 164, 256
 transmission line: *see* loudspeaker enclosure
 Transparent Audio: 286–287
 tri-amping: 82, 95
 Trifield: 328, 333–334
 Tube Trap: *see* Acoustic Sciences Corporation
 turntable
 choosing: 237–240
 drive system: 246, 251
 platter bearing: 246, 249
 sound quality: 237–243
 speed stability: 243, 251
 sprung: 247–248, 250, 261
 suspension: 246–249
 vacuum hold-down: 239, 249–250
 12 volt trigger: 61–62, 69
21st Century Vinyl: Michael Fremer's Practical Guide to Turntable Set-Up (DVD): 260
- ## U
- Ultralinear (tube operation): 114
 universal disc player: 167–168, 175–177
 upgrading components: 14, 16–17
 upsampling: 191, 196, 221
 USB (Universal Serial Bus): 8, 58, 74, 106, 178–179, 185–187, 189, 211, 214–215, 223, 225–2226, 28–229, 272, 303, 354, 356, 419, 426
 used equipment: 24–25
- ## V
- vacuum hold-down: *see* turntable
 vacuum tube
 bias adjustment: 92, 113, 418
 damper: 16, 407, 418
 installation and replacement: 66–68, 113–114, 418
 microphony in: 404, 415, 418, 422
 pentode: 98, 114, 493
 phono stage: 72
 power amplifiers: 92, 113–114
 preamplifier: 60, 65–68
 sound quality: 65–67, 92–93, 95, 98–100
 theory of operation: 112–115, 492–493
 300B: 98
 triode: 28, 85–86, 88, 90, 92, 98–101, 114, 492–493
 Valin, Jonathan: 44
 van den Hul: 258
 Vandersteen, Richard: 288
 Vandersteen Audio: 150, 288
 vented enclosure: *see* loudspeaker enclosure
 ventilation (of equipment): 409, 414–415, 424
 vertical tracking angle (VTA): 232, 261, 263
 vertical tracking force (VTF): 232, 259, 261, 411
 vertical venetian-blind effect: 135, 138
 Vibrapod: 424
 vibration: *see* resonance
 vinyl:
 comeback: 235–236
 45rpm: 254, 267–268
 half-speed mastering: 267

180-gram and 200-gram: 267–269

VTA: *see* vertical tracking angle

VTF: *see* vertical tracking force

W

Waldrep, Mark: 326

Walker, Peter: 134

Walker Audio: 250

warm-up (of equipment): 108, 196, 415, 419, 421

waterfall plots: *see* cumulative spectral decay

Water Lily Acoustics: 322

waveguide: 127, 142–143

WAV files: 220, 224, 228, 231, 354–355

webcasting: 182, 217

weighting curves: 435, 437

weighting filters: 435, 437

Well Tempered Laboratory: 253

Well Tempered Tonearm: 253

Western Electric 300B: 98

WiFi: 58, 188–189, 213–215, 229, 231, 354

Wilson, David: 264

Wilson Audio Specialties: 154, 264

Windows: 185, 221–224, 226–227

Windows Media Audio (WMA): 221, 224, 228

wireless audio: 8, 58, 84, 105–106, 167, 182, 188–
189, 213–215, 229–230, 297, 302, 355

WMA: *see* Windows Media Audio

wolf tone: 39, 152

word clock: 190–191, 453–454, 507–509

wow and flutter: 243, 251, 507

X

XLR connector: 62, 78, 179, 182, 184, 206–207,
229, 271–274, 280–282, 352, 408, 416–417

Z

zero-crossing distortion: 108

0dBFS: 503
